



MOLE DA RETTIFICA

Misure (diametro x spessore x foro)	Forma (+ ev. misure incavi)	Specifica	Utilizzo TA = tang. - TD = tondo
300x50x127	1	29A 46 H12 V161	TA - universale
350x50x127	1	29A 46 H12 V161	TA - universale
	5 - 210x10	13XHA 46 H11 V907F	TA - acc. temp. < 60 HRC
	5 - 210x10	23XA 46 I8 V907F	TA - acc. temp. > 55 HRC
	5 - 210x10	33XA 46 G11 V907F	TA - acc. temp. > 58 HRC
350x60x127	1	29A 46 H12 V907F	TA - universale
400x40x127	1	29A 54 K6 V161	TD - universale
	1	33XA 602 K6 V907F	TD - acc. temp. > 58 HRC
400x50x127	1	DRA 36 J8 V907F	TA - acc. dolce
	1	29A 46 H12 V907F	TA - universale
	1	29A 54 F12 V161	TA - acc. < 58 HRC
	5 - 210x10	13XHA 46 H12 V907F	TA - acc. temp. < 60 HRC
	5 - 210x10	33XA 46 G11 V907F	TA - acc. temp. > 58 HRC
	5 - 210x10	33XA 46 F11 V907F	TA - acc. temp. > 60 HRC
400x76x127	7 - 210x10/20	DRA 46 J8 V907F	TA - acc. dolce
	7 - 220x12/25	13XHA 46 H11 V907F	TA - acc. temp. > 60 HRC
	7 - 205x15/15	23XA 46 G11 V907F	TA - acc. temp. > 58 HRC
400x80x127	7 - 210x10/20	29A 46 H12 V907F	TA - universale
	7 - 215x17/20	23XA 46 I8 V907F	TA - acc. temp. > 55 HRC
400x80x152,4	7 - 220x10/20	23XA 46 I8 V907F	TA - acc. temp. > 55 HRC
450x30x127	1	29A 70 I10 V907F	TA e TD - profili
450x40x127	1	29A 70 I10 V907F	TA e TD - profili
450x63x127	1	29A 70 I10 V907F	TA e TD - profili
450x70x127	7 - 210x15	33XA 46 H10 V907F	TA - acc. temp. > 58 HRC
450x80x127	5 - 295x12,5	29A 70 I10 V907F	TA e TD - profili
450x80x203,2	7 - 285x15/15	23XA 46 I8 V907F	TA - acc. temp. > 58 HRC
	7 - 285x15/15	23XA 801 G9 V907F	TA - acc. temp. > 58 HRC

DAL 1882



MOLE ABRASIVI ERMOLI S.R.L.

Sede ed uffici:

Via Cairoli, 4 - 21046 - Malnate (VA)

Tel. 0332-425114 - Fax 0332-426742 - info@ermoli.it - www.ermoli.it

Stabilimento: Via Cairoli, 14 - 21046 Malnate (VA)

Tel 0332-426088



ISO 9001
Cert. n° 0704

Codice Fiscale e Partita IVA IT 00210280129 - Registro Imprese VA 2386 - R.E.A. Varese 5558

450x100x203,2	7 - 285x15/15	23XA 46 H9 V907F	TA - acc. temp. > 58 HRC
600x90x203,2	5 - 300x30	23XA 46 I8 V907F	TD - acc. temp. > 55 HRC
600x150x304,8	7 - 390x25/25	29A 46 K10 V907F	TA - universale
	7 - 390x25/25	23XA 46 G8 V907F	TA - acc. temp. > 58 HRC
700x100x305	5 - 440x15	23XA 46 I8 V907F	TD - acc. temp. > 55 HRC

N.B.: alle forma 1- 5 - è possibile inserire incavi o svasature a richiesta mediante tornitura

